
Technical specification: **mobile stage Speedi & Speedi Vario**

Speedi is the name of our space-saving stage element on fixed and steering castors which can be assembled in no time at all into an impressive stage. There is no need for a transport cart Speedi is highly agile due to its castors.

Features included:

- Stage floor is made of 5 layers of 21mm beech plywood, the surface layer is lacquered black and the special aluminium frame is bolted on securely from below
- Construction: jet black powder coated frame with electro plated moving parts
- Area load TÜV (TÜV=German Technical Inspection Agency) tested to DIN 1055 with 500 kg/m²
- Effective area of one element 125 x 250 cm
- Bearing surface approx. 45 x 125 cm
- Available as a fixed or variable height model
- Speedi has a fixed height and Speedi vario has variable heights of 40 and 60 cm or 60 and 80 cm.
- Legs of Speedi Vario have plastic feet with a diameter of 45 mm that allow the height to be adjusted by approx. 30 mm.
- Corners are pressed into robust aluminium brackets
- All round installation groove for rapid and secure attachment of accessories such as guard rails, step units etc.
- Quick linking wedges lock platforms together securely so there is no difference in height, even on uneven ground (Included in delivery)
- Available with different stage floors for indoor and outdoor use



Quick to set up thanks to solid mechanism.



The Speedi stage can be handled by just one person with minimal effort.